

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

EH4600PTA-WHITE

1. IDENTIFICATION

A. Product name

- EH4600PTA-WHITE

B. Recommended use and restriction on use

- General use : HEAVYDUTY EPOXY HIGH BUILD PRIMER
- Restriction on use : Do not use except for purpose

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : KCC Corporation
- Address : 30, Bangeojinsunhwando-ro, Dong-gu, Ulsan
- Emergency telephone number : 82-52-280-1717

○ Supplier/Distributor information

- Company name : KCC Corporation
- Address : 30, Bangeojinsunhwando-ro, Dong-gu, Ulsan
- Emergency telephone number : 82-52-280-1717

2. HAZARD IDENTIFICATION

A. GHS Classification

- Flammable liquids : Category3
- Acute toxicity (inhalation: vapor) : Category4
- Skin corrosion/irritation : Category2
- Serious eye damage/irritation : Category2
- Skin sensitization : Category1
- Germ cell mutagenicity : Category1B
- Carcinogenicity : Category1B
- Reproductive toxicity : Category2
- Specific target organ toxicity(Repeated exposure) : Category2
- Aspiration hazard : Category1
- Chronic aquatic toxicity : Category3

B. GHS label elements

○ Hazard symbols



○ Signal words

- Danger

- Hazard statements

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H340 May cause genetic defects
- H350 May cause cancer
- H361 Suspected of damaging fertility or the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure
- H412 Harmful to aquatic life with long lasting effects

- Precautionary statements

- 1) Prevention

- P201 Obtain special instructions before use.
 - P202 Do not handle until all safety precautions have been read and understood.
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P233 Keep container tightly closed.
 - P240 Ground and bond container and receiving equipment.
 - P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 - P242 Use non-sparking tools.
 - P243 Take action to prevent static discharges.
 - P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P264 Wash hands thoroughly after handling.
 - P271 Use only outdoors or in a well-ventilated area.
 - P272 Contaminated work clothing should not be allowed out of the workplace.
 - P273 Avoid release to the environment.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

- 2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 - P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 - P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P308+P313 If exposed or concerned: Get medical advice/attention.
 - P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 - P314 Get medical advice/attention if you feel unwell.
 - P321 Specific treatment (if in eyes, wash with plenty of running water; if in contact with skin, wash with plenty of running water; if inhaled, move to fresh air; if ingested, seek medical advice on whether to induce vomiting).
 - P331 Do NOT induce vomiting.
 - P332+P313 If skin irritation occurs: Get medical advice/attention.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P337+P313 If eye irritation persists: Get medical advice/attention.

- P362+P364 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

3) Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Titanium dioxide	Titanium oxide (Tio2) ; Titanium peroxide (Tio2) ; Dioxotitanium ; Pigment white 6	13463-67-7	31 ~ 38
4,4'-(1-Methylethylidene)bisphenol polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	Epi-Rez 5223	25036-25-3	13 ~ 20
Solvent naphtha (petroleum), light arom.	Naphtha	64742-95-6	7 ~ 14
Xylene	Xylol ; Methyltoluene	1330-20-7	7 ~ 14
Silica, vitreous	Silicon dioxide (vitreous) ; Fused silica ; Silica, amorphous, fused ;	60676-86-0	4 ~ 11
2,2-Bis(4'-glycidyoxyphenyl)propane	Diphenylol propane dicycidyl ether ; Bisphenol A diglycidyl ether ; Dimethylmethane diglycidyl ether ; 2,2-bis(4-(2,3-Epoxypropoxy)phenyl) propane ; 2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; 4,4'-Bis(2,3-epoxypropoxy)diphenyldimethylmethane ; Bis(4-hydroxyphenyl)dimethylmethane diglycidyl ether ; Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis- ; 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Bisphenol A diglycidyl ether	1675-54-3	4 ~ 11
Aluminium oxide	Alpha-alumina ; Beta-alumina ; Gamma-alumina ; Alpha-aluminum oxide ; Beta-aluminum oxide ; Gamma-aluminum oxide ; Delta-aluminum oxide ; Aluminium trioxide ;	1344-28-1	1 ~ 8
Ethylbenzene	Benzene, ethyl- ; Ethyl benzene ; Ethylbenzol ; Phenylethane ;	100-41-4	1 ~ 6
Propylene glycol methyl ether	1-Methoxy-2-hydroxypropane ; 2-Methoxy-1-methylethanol ; Alpha-propylene glycol monomethyl ether ; 1-Methoxy-2-propanol ; Propylene glycol methyl ether ; 1-Methoxy-propane-2-ol ; Methoxyisopropanol	107-98-2	1 ~ 6
Urea, polymer with formaldehyde, isobutylated	ISOBUTYLATED UREA FORMALDEHYDE	68002-18-6	1 ~ 6

Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester	Decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester ; Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester ; bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; Bis(1,2,2,6,6-pentamethyl-4-piperidyl) decanedioate ; Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester ; DECANEDIOATE, BIS(1,2,2,6,6-PENTAMETHYL-4- PIPERIDINYL) (PICCS) ; BIS(1,2,2,6,6-PENTAMETHYL-4- PIPERIDINYL)SEBACATE ; Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate ; Bis(1,2,2,6,6-pentamethyl-4-piperidyl) 1,8-octanedicarboxylate ; Bis(N-methyl-2,2,6,6-tetramethyl-4-piperidiny)	41556-26-7	0.1~1
--	--	------------	-------

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

B. Specific hazards arising from the chemical

- Causes serious eye irritation
- Causes skin irritation
- Flammable liquid and vapour
- Harmful if inhaled
- Harmful to aquatic life with long lasting effects

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

○ ACGIH TLV

- [Titanium dioxide] : TWA 0.2 mg/m³ (Nanoscale particles), 2.5 mg/m³ (Finescale particles) Respirable particulate

mass

- [Xylene] : TWA 20 ppm
- [Aluminium oxide] : TWA 10 mg/m³
- [Ethylbenzene] : TWA, 20 ppm (87 mg/m³)
- [Propylene glycol methyl ether] : TWA, 50 ppm (184 mg/m³), STEL, 100 ppm (369 mg/m³)

○ OSHA PEL

- [Titanium dioxide] : 15 mg/m³ (Total dust)
- [Xylene] : 100 ppm, 435 mg/m³
- [Silica, vitreous] : 80 mg/m³ (%SiO₂)
- [Aluminium oxide] : 15 mg/m³ (Total dust), 5 mg/m³ (Respirable fraction)
- [Ethylbenzene] : 100 ppm, 435 mg/m³

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

○ Respiratory protection

- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Respiratory protection is ranked in order from minimum to maximum.
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- Consider warning properties before use.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

○ Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ Hand protection

- Wear appropriate chemical resistant glove.

○ Skin protection

- Wear appropriate chemical resistant protective clothing.

○ Others

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	WHITE
B. Odor	Smell of liquor
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	32°C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available

J. Upper/Lower Flammability or explosive limits	1 % / 14 %
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	> 1(Air=1)
N. Specific gravity(Relative density)	1.516 ~ 1.556
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	343°C
Q. Decomposition temperature	Not available
R. Viscosity	105 ~ 115 KU
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Sparks, flames, static electricity, strong acids and base substances

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- ☐ Respiratory tracts
 - May be fatal if swallowed and enters airways
- ☐ Oral
 - Not available
- ☐ Eye-Skin
 - Causes skin irritation
 - May cause an allergic skin reaction

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- ☐ Acute toxicity
 - * Oral
 - Product (ATEmix) : 2000mg/kg < ATEmix <= 5000mg/kg
 - [Titanium dioxide] : LD50 >5000 mg/kg Mouse (OECD TG 420) (OECD SIDS)
 - [Solvent naphtha (petroleum), light arom.] : LD50 > 5000 mg/kg Rat (Read across 86290-81-5)(OECD TG 401,GLP)(ECHA)
 - [Xylene] : LD50 3523 mg/kg Rat (EU Method B.1) (ECHA)
 - [2,2-Bis(4'-glycidyoxyphenyl)propane] : LD50 > 2000 mg/kg Rat(female) (OECD TG 420, GLP) (ECHA)
 - [Aluminium oxide] : LD50 > 10000 mg/kg Rat (OECD TG 401) (ECHA)
 - [Ethylbenzene] : LD50 3500 mg/kg Rat (ECHA)
 - [Propylene glycol methyl ether] : LD50 4016 mg/kg Rat (EU Method B.1, GLP) (ECHA)
 - * Dermal

- Product (ATEmix) : 2000mg/kg < ATEmix <= 5000mg/kg
- [Solvent naphtha (petroleum), light arom.] : LD50 > 2000 mg/kg Rabbit (Read across 86290-81-5)(OECD TG 402, GLP)(ECHA)
- [Xylene] : LD50 1700 mg/kg Rabbit (EPA Pesticide, 2005) (NITE), Acute toxicity - dermal EU Harmonized Cat. 4 (ECHA)
- [2,2-Bis(4'-glycidyoxyphenyl)propane] : LD50 > 2000 mg/kg Rat, No Death (OECD TG 402, GLP) (ECHA)
- [Ethylbenzene] : LD50 15432 mg/kg (17.8 mL/kg) Rabbit (ECHA)
- [Propylene glycol methyl ether] : LD50 > 2000 mg/kg Rat (EU Method B.3, GLP) (ECHA)
- * Inhalation
 - Product (ATEmix) : 10.0mg/L 4hr < ATEmix <= 20.0mg/L 4hr
 - [Titanium dioxide] : Aerosol LC50 5.09 mg/L 4h Rat No death, Not classified (ECHA)
 - [Solvent naphtha (petroleum), light arom.] : Vapour LC50 > 7.63 mg/L Rat 4hr (Read across 86290-81-5)(OECD TG 403, GLP)(ECHA)
 - [Xylene] : Vapor LC50 10~20 mg/L 4 hr (NIER), Acute toxicity - inhalation EU Harmonized Cat. 4 (ECHA)
 - [Aluminium oxide] : Aerosol LC50 > 2.3 mg/L 4hr Rat No death Not classified (OECD TG 403, GLP) (ECHA)
 - [Ethylbenzene] : Vapor LC50 18.96 mg/L 4 hr Rat (NIER)
 - [Propylene glycol methyl ether] : Vapor LC0 > 8573 ppm 4hr (7000 ppm 6 hr) Rat No death Not classified (OECD TG 403, GLP) (ECHA)
- Skin corrosion/irritation
 - Causes skin irritation
- Serious eye damage/irritation
 - Causes serious eye irritation
- Respiratory sensitization
 - Not available
- Skin sensitization
 - May cause an allergic skin reaction
- Carcinogenicity
 - * IARC
 - [Titanium dioxide] : Group 2B
 - ※ IARC (International Agency for Research on Cancer) has classified TiO₂ as a substance which may be possibly carcinogenic to humans. However, studies on TiO₂ conducted by the IARC state that when TiO₂ is mixed in substance such as paints and coatings, the level of exposure is not severe. An increase in cancer was found only when ultrafine TiO₂ particles of less than 100nm were used in a Study on Long-term Inhalation of TiO₂ by Animals, issued by the National Institute for Occupational Safety & Health (NIOSH). Therefore, it is difficult to conclude that this product, which contains TiO₂ with a particle size of 280~360nm, can be carcinogenic enough to cause cancer.
 - [Xylene] : Group 3
 - [Silica, vitreous] : Group 3 (Silica, amorphous)
 - [2,2-Bis(4'-glycidyoxyphenyl)propane] : Group 3
 - [Ethylbenzene] : Group 2B
 - * OSHA
 - Not available
 - * ACGIH
 - [Titanium dioxide] : A3
 - [Xylene] : A4
 - [Aluminium oxide] : A4 (Aluminum insoluble compounds)
 - [Ethylbenzene] : A3
 - [Propylene glycol methyl ether] : A4
 - * NTP
 - Not available

* EU CLP

- [Titanium dioxide] : Carc. 2
- [Solvent naphtha (petroleum), light arom.] : Carc. 1B (Note P)
- Germ cell mutagenicity
 - May cause genetic defects
- Reproductive toxicity
 - Suspected of damaging fertility or the unborn child
- STOT-single exposure
 - Not available
- STOT-repeated exposure
 - May cause damage to organs through prolonged or repeated exposure
- Aspiration hazard
 - May be fatal if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- Fish
 - [Titanium dioxide] : LC50 >100 mg/L 96 hr *Carassius auratus*, *Oncorhynchus mykiss* (ECHA)
 - [Solvent naphtha (petroleum), light arom.] : LL50 8.2 mg/L 96hr *Pimephales promelas* (Read-across Light alkylate naphtha) (EPA 66013-75-009, GLP), NOELR 2.6 mg/L 14d *Pimephales promelas* (Read-across Light Catalytically Reformed Naphtha) (OECD TG 204, GLP) (ECHA)
 - [Xylene] : LC50 7.6 mg/L 96 hr *Oncorhynchus mykiss* (Read-across 95-47-6) (OECD TG 203) (ECHA), NOEC 0.714 mg/L 35 d *Danio rerio* (Read-across 106-42-3) (OECD TG 210, GLP) (ECHA)
 - [2,2-Bis(4'-glycidyloxyphenyl)propane] : LC50 1.5 mg/L 96 hr *Oncorhynchus mykiss* (OECD TG 203, ECHA)
 - [Aluminium oxide] : LC50 114.97 mg/L 96 hr *Channa marulius* (Read across CAS No. 7446-70-0) (ECHA)
 - [Ethylbenzene] : LC50 4.2 mg/L 96 hr *Oncorhynchus mykiss* (NIER)
 - [Propylene glycol methyl ether] : LC50 4600~10000 mg/L 96 hr *Leuciscus idus* (ECHA)
 - [Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester] : LC50 0.34 mg/L 96hr *Lepomis macrochirus* (OECD TG 203) (IUCLID)
- Crustaceans
 - [Titanium dioxide] : EC50 >100 mg/L 48 hr *Daphnia magna*, OECD TG 202 (ECHA)
 - [Solvent naphtha (petroleum), light arom.] : EL50 4.5 mg/L 48hr *Daphnia magna* (Read-across straight-run light gasoline) (OECD TG 202, GLP), NOELR 2.6 mg/L 21d (Read-across Light alkylate naphtha) (OECD TG 211, GLP) (ECHA)
 - [Xylene] : EC50 4.7 mg/L 48 hr *Daphnia magna* (Read-across 108-38-3) (NIER), NOEC 1.17 mg/L 7 d *Ceriodaphnia dubia* (ECHA)
 - [2,2-Bis(4'-glycidyloxyphenyl)propane] : EC50 1.7 mg/L 48 hr *Daphnia magna* (OECD TG 202, GLP), NOEC 0.3 mg/L 21d *Daphnia magna* (OECD TG 211, GLP) (ECHA)
 - [Aluminium oxide] : LC50 306.89 mg/L 48 hr *Melanoides tuberculata*, NOEC 4.9 mg/L 8 d *Ceriodaphnia* sp. (ECHA)
 - [Ethylbenzene] : EC50 1.8~2.4 mg/L 48 hr *Daphnia magna*, NOEC 0.96 mg/L 7 d *Ceriodaphnia dubia* (ECHA)
 - [Propylene glycol methyl ether] : LC50 21100~25900 mg/L 48 hr *Daphnia magna* (ECHA)
- Algae
 - [Titanium dioxide] : ErL50 > 100 mg/ℓ 72 hr *Pseudokirchneriella subcapitata*, growth rate, static, (72h-EyL50 >100 mg/L static, OECD TG 201) (ECHA)
 - [Solvent naphtha (petroleum), light arom.] : EL50 3.1 mg/L, NOELR 0.5 mg/L 72hr *Selenastrum capricornutum* (Read-across Blended Gasoline) (OECD TG 201, GLP) (ECHA)
 - [Xylene] : EC50 4.7 mg/L 72 hr *Raphidocelis subcapitata* (Read-across 95-47-6) (OECD TG 201) (ECHA)
 - [2,2-Bis(4'-glycidyloxyphenyl)propane] : EC50 > 11 mg/L 72 hr, NOEC 4.2 mg/L 72 hr *Scenedesmus capricornutum* (EPA-660/3-75-009, ECHA)
 - [Aluminium oxide] : EC50 > 0.103 mg/L 72 hr *Raphidocelis subcapitata* (OECD TG 201, GLP) (ECHA)
 - [Ethylbenzene] : EC50 3.6 mg/L 96 hr, NOEC 3.4 mg/L 96 hr *Raphidocelis subcapitata* (ECHA)
 - [Propylene glycol methyl ether] : EC50 > 1000 mg/L 96 hr *Raphidocelis subcapitata* (OECD TG 201, GLP) (ECHA)

B. Persistence and degradability

○ Persistence

- [Xylene] : log Pow 3.12 (Read-across 95-47-6) (ECHA)
- [2,2-Bis(4'-glycidyoxyphenyl)propane] : log Kow 2.64 ~ 3.78 (25 °C, pH ca. 7) (OECD TG 117, GLP) (ECHA)
- [Ethylbenzene] : log Pow 3.6 (20 °C) (ECHA)
- [Propylene glycol methyl ether] : log Pow < 1 (20 °C) (OECD TG 117) (ECHA)

○ Degradability

- Not available

C. Bioaccumulative potential

○ Bioaccumulative potential

- [Xylene] : BCF 25.9 dimensionless (ECHA)
- [Ethylbenzene] : BCF 1 (ECHA)

○ Biodegradation

- [Xylene] : Readily biodegradable, 94 % 28 d (O2 consumption) (Read-across 95-47-6) (OECD TG 301 F, GLP) (ECHA)
- [2,2-Bis(4'-glycidyoxyphenyl)propane] : Not readily biodegradable, 5 % degradation (O2 consumption) 28 day (ECHA)
- [Ethylbenzene] : Readily biodegradable, 70~ 80 % 28 d (inorg. C analysis) (ISO 14593-CO2-Headspace Test) (ECHA)
- [Propylene glycol methyl ether] : 96 % 28 d, Readily biodegradable (OECD TG 301 E, GLP) (ECHA)
- [Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester] : 38 (%) 28 d (IUCLID)

D. Mobility in soil

- [Xylene] : log Koc ca. 2.73 dimensionless (Read-across 95-47-6) (OECD TG 121) (ECHA)

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- It shall be treated by incineration
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1263

B. Proper shipping name

- PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)(Solvent naphtha (petroleum), light arom.)

C. Hazard Class

- 3

D. IMDG CODE/IATA DGR Packing group

- III

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ POPs Management Law

- [Titanium dioxide] : Not applicable
- [4,4'-(1-Methylethylidene)bisphenol polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]] : Not applicable
- [Solvent naphtha (petroleum), light arom.] : Not applicable
- [Xylene] : Not applicable
- [Silica, vitreous] : Not applicable
- [2,2-Bis(4'-glycidyoxyphenyl)propane] : Not applicable
- [Aluminium oxide] : Not applicable
- [Ethylbenzene] : Not applicable
- [Propylene glycol methyl ether] : Not applicable
- [Urea, polymer with formaldehyde, isobutylated] : Not applicable
- [Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester] : Not applicable

○ Information of EU Classification

* Classification

- [Solvent naphtha (petroleum), light arom.] : H304,H340,H350
- [Xylene] : H226,H312,H315,H332
- [2,2-Bis(4'-glycidyoxyphenyl)propane] : H315,H317,H319
- [Ethylbenzene] : H225,H304,H332,H373
- [Propylene glycol methyl ether] : H226,H336

○ U.S. Federal regulations

* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable

* CERCLA Section 103 (40CFR302.4)

- [Xylene] : 45.3599 kg 100 lb
- [Ethylbenzene] : 453.599 kg 1000 lb
- [Titanium dioxide] : Not applicable
- [4,4'-(1-Methylethylidene)bisphenol polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]] : Not applicable
- [Solvent naphtha (petroleum), light arom.] : Not applicable
- [Silica, vitreous] : Not applicable
- [2,2-Bis(4'-glycidyoxyphenyl)propane] : Not applicable
- [Aluminium oxide] : Not applicable
- [Propylene glycol methyl ether] : Not applicable
- [Urea, polymer with formaldehyde, isobutylated] : Not applicable
- [Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester] : Not applicable

* EPCRA Section 302 (40CFR355.30)

- Not applicable
- * EPCRA Section 304 (40CFR355.40)
 - Not applicable
- * EPCRA Section 313 (40CFR372.65)
 - [Xylene] : Applicable
 - [Aluminium oxide] : Applicable
 - [Ethylbenzene] : Applicable
 - [Titanium dioxide] : Not applicable
 - [4,4'-(1-Methylethylidene)bisphenol polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]] : Not applicable
 - [Solvent naphtha (petroleum), light arom.] : Not applicable
 - [Silica, vitreous] : Not applicable
 - [2,2-Bis(4'-glycidyoxyphenyl)propane] : Not applicable
 - [Propylene glycol methyl ether] : Not applicable
 - [Urea, polymer with formaldehyde, isobutylated] : Not applicable
 - [Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester] : Not applicable
- ☐ Rotterdam Convention listed ingredients
 - Not applicable
- ☐ Stockholm Convention listed ingredients
 - Not applicable
- ☐ Montreal Protocol listed ingredients
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2020-12-01

C. Revision number and Last date revised

- 9 times, 2025-06-10

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).