

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

RV490-9000

1. IDENTIFICATION

A. Product name

- RV490-9000

B. Recommended use and restriction on use

- General use : Hydrocarbon based temporary rust-preventing primer
- Restriction on use : Do not use except for purpose

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : KCC Corporation
- Address : 30, Bangeojinsunhwando-ro, Dong-gu, Ulsan
- Emergency telephone number : 82-52-280-1717

○ Supplier/Distributor information

- Company name : KCC Corporation
- Address : 30, Bangeojinsunhwando-ro, Dong-gu, Ulsan
- Emergency telephone number : 82-52-280-1717

2. HAZARD IDENTIFICATION

A. GHS Classification

- Flammable liquids : Category3
- Acute toxicity (dermal) : Category5
- Skin corrosion/irritation : Category2
- Germ cell mutagenicity : Category1B
- Carcinogenicity : Category1B
- Specific target organ toxicity(Repeated exposure) : Category1
- Aspiration hazard : Category1
- Acute aquatic toxicity : Category3
- Chronic aquatic toxicity : Category3

B. GHS label elements

○ Hazard symbols



○ Signal words

- Danger

○ Hazard statements

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H313 May be harmful if contact with skin.
- H315 Causes skin irritation
- H340 May cause genetic defects
- H350 May cause cancer
- H372 Causes damage to organs through prolonged or repeated exposure
- H402 Harmful to aquatic organisms.
- H412 Harmful to aquatic life with long lasting effects

○ Precautionary statements

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P312 IF ON SKIN: Call a POISON CENTER/doctor if you feel unwell.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

3) Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
---------------	--------------------------	---------	------------

Petroleum resins	Neopolymer (petroleum resin) ; Hydrocarbon resin ; Hydrocarbons, petroleum resins ;	64742-16-1	52 ~ 59
Naphtha (petroleum), hydrodesulfurized heavy	Aliphatic hydrocarbon ; Oils, naphtha, hydrodesulfurized heavy ; Hydrodesulfurized heavy naphtha (petroleum) ;	64742-82-1	37 ~ 44
Solvent naphtha (petroleum), light arom.	Naphtha	64742-95-6	1 ~ 8
4-Morpholinecarbaldehyde	4-Formylmorpholine;Morpholine, 4-formyl-	4394-85-8	0.1~1

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

B. Specific hazards arising from the chemical

- Causes damage to organs through prolonged or repeated exposure
- Causes skin irritation
- Flammable liquid and vapour
- Harmful to aquatic life with long lasting effects
- Harmful to aquatic organisms.

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- ACGIH TLV
 - Not applicable
- OSHA PEL
 - Not applicable

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

- Respiratory protection
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).

- Any chemical cartridge respirator with organic vapor cartridge(s).
- Consider warning properties before use.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Respiratory protection is ranked in order from minimum to maximum.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Eye protection
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Hand protection
 - Wear appropriate chemical resistant glove.
- Skin protection
 - Wear appropriate chemical resistant protective clothing.
- Others
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	CLEAR
B. Odor	Solvent odor
C. Odor threshold	NO DATA
D. pH	Not available
E. Melting point/Freezing point	NO DATA
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	38°C
H. Evaporation rate	NO DATA
I. Flammability(solid, gas)	NO DATA
J. Upper/Lower Flammability or explosive limits	1%/5%
K. Vapour pressure	NO DATA
L. Solubility	NO DATA
M. Vapour density	> 1(Air=1)
N. Specific gravity(Relative density)	0.902 ~ 0.942
O. Partition coefficient of n-octanol/water	NO DATA
P. Autoignition temperature	210
Q. Decomposition temperature	NO DATA
R. Viscosity	54 ~ 60 KU
S. Molecular weight	NO DATA

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Sparks, flames, static electricity, strong acids and base substances

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- ☐ Respiratory tracts
 - May be fatal if swallowed and enters airways
- ☐ Oral
 - Not available
- ☐ Eye-Skin
 - Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- ☐ Acute toxicity
 - * Oral
 - Product (ATEmix) : >5000mg/kg
 - [Petroleum resins] : LD50 > 2000 mg/kg Rat (OECD TG 423, GLP)
 - [Naphtha (petroleum), hydrodesulfurized heavy] : LD50 > 5000 mg/kg Rat (ECHA)
 - [Solvent naphtha (petroleum), light arom.] : LD50 = 8400 mg/kg Rat (RTECS)
 - [4-Morpholinecarbaldehyde] : LD50 6500 mg/kg Rat (ChemIDPlus)
 - * Dermal
 - Product (ATEmix) : 2000mg/kg < ATEmix <= 5000mg/kg
 - [Naphtha (petroleum), hydrodesulfurized heavy] : LD50 >3160 mg/kg Rabbit (IUCLID)
 - [Solvent naphtha (petroleum), light arom.] : LD50 > 2000 mg/kg Rabbit (IUCLID)
 - [4-Morpholinecarbaldehyde] : LD50 46000 mg/kg Rabbit (ChemIDPlus)
 - * Inhalation
 - Product (ATEmix) : Not available
 - [Naphtha (petroleum), hydrodesulfurized heavy] : Vapor LC50 > 7.63 mg/L/4hr No death, Not classified (ECHA)
 - [Solvent naphtha (petroleum), light arom.] : Vapor LC50 > 5.61 mg/L 4 hr Rat (Read-across: 86290-81-5) No death (ECHA)
- ☐ Skin corrosion/irritation
 - Causes skin irritation
- ☐ Serious eye damage/irritation
 - Not available
- ☐ Respiratory sensitization
 - Not available
- ☐ Skin sensitization
 - Not available
- ☐ Carcinogenicity
 - * IARC
 - Not available
 - * OSHA
 - Not available
 - * ACGIH

- Not available
- * NTP
 - Not available
- * EU CLP
 - [Naphtha (petroleum), hydrodesulfurized heavy] : Carc. 1B (Note P)
 - [Solvent naphtha (petroleum), light arom.] : Carc. 1B (Note P)
- Germ cell mutagenicity
 - May cause genetic defects
- Reproductive toxicity
 - Not available
- STOT-single exposure
 - Not available
- STOT-repeated exposure
 - Causes damage to organs through prolonged or repeated exposure
- Aspiration hazard
 - May be fatal if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- Fish
 - [Solvent naphtha (petroleum), light arom.] : LC50 = 9.22 mg/l 96 hr *Oncorhynchus mykiss* (IUCLID)
 - [4-Morpholinecarbaldehyde] : LC50 > 500 mg/l 96hr *Leuciscus idus* (ECHA)
- Crustaceans
 - [Petroleum resins] : EC50 > 100mg/l 48hr *Daphnia magna* (OECD TG 202, GLP) (ECHA)
 - [Naphtha (petroleum), hydrodesulfurized heavy] : LC50 4.3 mg/l 96 hr other(*Crangon crangon*) (IUCLID)
 - [Solvent naphtha (petroleum), light arom.] : EC50 = 6.14 mg/l 48 hr *Daphnia magna* (IUCLID)
 - [4-Morpholinecarbaldehyde] : EC50 > 500 mg/l 48hr *Daphnia magna* (ECHA)
- Algae
 - [Petroleum resins] : EC50 > 100mg/l 72hr *Desmodesmus subspicatus* (OECD TG 201, GLP) (ECHA)
 - [Solvent naphtha (petroleum), light arom.] : EC50 = 19 mg/l 72 hr *Selenastrum capricornutum* (IUCLID)
 - [4-Morpholinecarbaldehyde] : EC50 23880 mg/l 72hr *Desmodesmus subspicatus* (ECHA)

B. Persistence and degradability

- Persistence
 - [Naphtha (petroleum), hydrodesulfurized heavy] : 6 log Kow ~ 2.1 log Kow (Estimate) (IUCLID)
 - [Solvent naphtha (petroleum), light arom.] : log Kow = 2.1 ~ 6 (Estimate) (IUCLID)
 - [4-Morpholinecarbaldehyde] : log Kow -1.2 (ECHA)
- Degradability
 - [Solvent naphtha (petroleum), light arom.] : BOD5/COD = 0.43

C. Bioaccumulative potential

- Bioaccumulative potential
 - [4-Morpholinecarbaldehyde] : BCF < 1 OECD Guideline 305 C (ECHA)
- Biodegradation
 - [Petroleum resins] : Not readily biodegradable 18 % 28 d (CO2 evolution) (OECD TG 301 B, GLP) (ECHA)
 - [4-Morpholinecarbaldehyde] : Readily biodegradable OECD Guideline 301 A (ECHA)

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- It shall be treated by incineration
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1263

B. Proper shipping name

- PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)

C. Hazard Class

- 3

D. IMDG CODE/IATA DGR Packing group

- III

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ POPs Management Law

- [Petroleum resins] : Not applicable
- [Naphtha (petroleum), hydrodesulfurized heavy] : Not applicable
- [Solvent naphtha (petroleum), light arom.] : Not applicable
- [4-Morpholinecarbaldehyde] : Not applicable

○ Information of EU Classification

* Classification

- [Naphtha (petroleum), hydrodesulfurized heavy] : H304,H340,H350,H372
- [Solvent naphtha (petroleum), light arom.] : H304,H340,H350

○ U.S. Federal regulations

* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable

* CERCLA Section 103 (40CFR302.4)

- Not applicable

* EPCRA Section 302 (40CFR355.30)

- Not applicable

* EPCRA Section 304 (40CFR355.40)

- Not applicable

* EPCRA Section 313 (40CFR372.65)

- Not applicable

○ Rotterdam Convention listed ingredients

- Not applicable

○ Stockholm Convention listed ingredients

- Not applicable

○ Montreal Protocol listed ingredients

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2013-03-29

C. Revision number and Last date revised

- 6 times, 2024-02-13

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).